

Since 1898
CONSEW®


146RB Series

MODELS: 146RB-1A-1/146RB-2A-1/146RB-3A-1

146RBL Long Arm in configurations as above but with up to 30" arm length

With
 HORIZONTAL AXIS TRANSVERSE ROTARY HOOK
 LARGE BOBBIN
 WIDE ZIG-ZAG
 REVERSE FEED

SEE REVERSE SIDE
 FOR MACHINES
 FEATURING STITCH
 TYPES 304, 308
 LONG ARM AND
 WETSUIT VERSIONS



146RB-1A-1

SINGLE NEEDLE
 DROP FEED
 WALKING FOOT
ZIG-ZAG
 LOCKSTITCH MACHINE



146RBL
 Up to 30" Long Arm
 in 1A, 2A or 3A configuration
 (special order)

146 RBL LONG ARM VERSION (up to 30")
 Also available for WET SUIT material - (WS)

***Interchangeable between 1A, 2A, 3A Stitches
 by changing gears and cams. (Comes with one set, other sets optional)***

ZIG ZAG

**Models: 146RB-1A-1/146RB-2A-1/146RB-3A-1
146RBL Long Arm up to 30" (special order as a 1A, 2A or 3A)**

APPLICATIONS

146RB-1A-1 – For sewing medium to heavy weight fabrics that are difficult to feed when sewn.

- For such materials and products as wet suits, shoes, boots, leather, tarpaulins. Federal Stitch 304

146RB-2A-1 – Three step/two stitch zig-zag


- For sewing elastic and other stretch materials
- For stitching such products as boat and truck covers, tents, awnings, sails, parachutes, tarpaulins and similar products
- Used on such materials as canvas, nylon, vinyl, leather, synthetics and similar materials.
- Especially desirable where reinforced stitch is necessary. Federal Stitch 308

146RB-3A-1 – Four step/three stitch zig-zag

- Performs similar operations as Model 146RB-2A with the added advantage of making an additional stitch for extra reinforcement.

146RBL – Same subclasses as above but with long arm. Long arm can be special ordered up to 30"

WS – Wet Suit version available for sewing neoprene rubber



FEATURES

- Large bobbin and horizontal axis transverse rotary hook
- Upper feed mechanism helps avoid slippage when sewing
- Stitches per minute - 2500*
- Optional: Interchangeable between 1A, 2A & 3A stitches; Additional parts required (not included).
- Wide zig-zag
- Reverse stitching

SPECIFICATIONS

Speed, Max. (S.P.M.) *	2500	Hook	B79
Clearance Under Foot	25/64" (10 mm)	Bed Size	Model 146RB-1A-1 7" X 18 7/8" (178 x 480 mm)
Needle Bar Stroke	1-11/32" (34 mm)		Model 146RBL-USA 7" x ___" (178 x ___ mm)
Stitch Length, Max.	5 s.p.i. (5 mm)	Work Space	Model 146RB-1A-1 10" (255 mm)
Needle	135 X 17		Model 146RBL-USA Up to 30" special order
Bobbin	Metal	Zig-Zag Stitch Width, Max.	3/8" (9.5 mm)
	Pre-wound		

* Speed depends on width of zig-zag, material and thread.

BILLS SEWING MACHINE CO
301 MAIN AVE EAST
HILDEBRAN, NC 28637
BRS@BILLSEWING.COM
WWW.BILLSEWING.COM
(828) 397-6941 (828) 328-5816